

INSTRUMENTATION CABLE
Cu, PVC insulated, individual and overall screen, PVC bedding, DSTA, PVC outer sheath
IEC60332.1

Type	R-Cu/PVC/IS/OS/PVC/DSTA/PVC 300/500V RR2XHOHRNR 300/500V	3X3X 1sqmm
Conductor :	Stranded plain copper conductor according to IEC60228 cl.2 size 1sqmm (7x0,43) Diam. 1,3 mm	
Insulation :	PVC extruded compound Thickness : 0,5 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Blue - Brown - Black numbered (or to be agreed)	
Pair/Triad screen	Applied over the single pair/triad will be wrapped with polyester tape and shielded with Aluminum / Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm, over the screen will be placed a further Mylar tape.	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armour :	STA, Double galvanized steel tape Thickness : 0,25 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue (or to be agreed) Thickness : 1,6 mm Overall diameter : 19 mm Total weight : 550 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 18,1 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332.1, CEI20-35 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 14 V. D. - Hydrocarbon and UV resistant - Inductance <= 0,90 mH/Km - Capacitance <= 0,250 microF/Km	

Weight and diameter are theoretical + / - 10%