

**INSTRUMENTATION CABLE  
Cu, PVC insulated, overall screen, PVC outer sheath  
IEC60332.3, EN50288-7**

---

<b>Type</b>	<b>R-Cu/PVC/OS/PVC 300/500V RR2OHR 300/500V</b>	<b>2X 1sqmm</b>
<b>Conductor :</b>	Stranded plain copper conductor according to IEC60228 cl.2 size 1sqmm ( 7x0,43 ) Diam. 1,3 mm	
<b>Insulation :</b>	PVC extruded compound Thickness : 0,5 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to pair, color White - Black ( or to be agreed )	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue ( or to be agreed ) Thickness : 1,2 mm Overall diameter : 7,4 mm Total weight : 80 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	<ul style="list-style-type: none"><li>- Conductor resistance 18,1 ohm/Km ( + 5% for multipair )</li><li>- Test voltage core to core 2 Kv</li><li>- Flame retardant according to IEC60332-3-24, CEI20-22/3</li><li>- Low smoke and fume as per IEC60754-1, CEI20-37</li><li>- HCL emission <math>\leq</math> 22%</li><li>- Minimum bending radius 8 V. D.</li><li>- Hydrocarbon and UV resistant</li><li>- Cable for intrinsically safe application</li><li>- Inductance <math>\leq</math> 0,90 mH/Km</li><li>- Capacitance <math>\leq</math> 0,250 microF/Km</li><li>- This cable is suitable to be used in ATEX area following the EN60079-14 prescription</li></ul>	

**Weight and diameter are theoretical + / - 10%**