

INSTRUMENTATION CABLE
Cu, PVC insulated, overall screen, PVC outer sheath
IEC60332.1, IEC60332.3

Type **R-Cu/PVC/OS/PVC 300/500V**
RR2XOHR 300/500V**Conductor :** Stranded plain copper conductor according to IEC60228 cl.2 size 1sqmm (7x0,43)
Diam. 1,3 mm**Insulation :** PVC extruded compound - Temperature range -15 + 80°C
Thickness : 0,5 mm - Temperature laying -5 + 70°C**Laying up :** Twisted to pairs, Blue - Black numbered (or to be agreed)**Overall screen** Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar
tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire
7x0,30 size 0,5sqmm.**Outer sheath :** PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Grey (or to be agreed)**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance : - Conductor resistance 18,1 ohm/Km (+ 5% for multipair)
- Test voltage core to core 2 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission \leq 22%
- Hydrocarbon and UV resistant

- Inductance \leq 0,90 mH/Km
- Capacitance \leq 0,250 microF/Km

INSTRUMENTATION CABLE
Cu, PVC insulated, overall screen, PVC outer sheath
IEC60332.1, IEC60332.3

Technical data & Electrical properties at 20°C

DESCRIPTION	Sheath thickness	Ext.Dia m mm	W. Kg/Km	Armour Diam.	Bending radius
R-Cu/PVC/OS/PVC 300/500V 2X1	1,2	7,4	80		59
R-Cu/PVC/OS/PVC 300/500V 2X2X1	1,2	8,5	120		68
R-Cu/PVC/OS/PVC 300/500V 4X2X1	1,4	13,3	240		106
R-Cu/PVC/OS/PVC 300/500V 8X2X1	1,6	17	400		136
R-Cu/PVC/OS/PVC 300/500V 12X2X1	1,6	21	570		168
R-Cu/PVC/OS/PVC 300/500V 16X2X1	1,8	23	710		184

Weight and diameter are theoretical +/- 10%