

INSTRUMENTATION CABLE
Cu, PVC insulated, overall screen, PVC bedding, DSTA, PVC outer sheath
IEC60332.3-24

Type	R-Cu/PVC/OS/PVC/DSTA/PVC 250V RR2OHRNR 250V	9G 1,5sqmm
Conductor :	Stranded plain copper conductor according to IEC60228 cl.2 size 1,5sqmm (7x0,53) Diam. 1,55 mm	
Insulation :	PVC extruded compound Thickness : 0,5 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color Black numbered Y/G (or to be agreed)	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armour :	STA, Double galvanized steel tape Thickness : 0,2 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Blue (or to be agreed) Thickness : 1,8 mm Overall diameter : 18 mm Total weight : 880 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 12,1 ohm/Km (+ 5% for multipair) - Test voltage core to core 1,5 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission \leq 22% - Minimum bending radius 16 V. D. - Hydrocarbon and UV resistant	

Weight and diameter are theoretical + / - 10%