

INSTRUMENTATION CABLE
Cu, PVC insulated, overall screen, PVC bedding, SWA, PVC outer sheath
IEC60332.3, EN50288-7

Type	R-Cu/PVC/OS/PVC/SWA/PVC 300/500V RR2OHRFR 300/500V	3X 1,5sqmm
Conductor :	Stranded red copper conductor according to IEC60228 cl.2 size 1,5sqmm (7x0,53) Diam. 1,55 mm	
Insulation :	PVC extruded compound Thickness : 0,5 mm	- Temperature range -15 + 80°C - Temperature laying -5 + 70°C
Laying up :	Twisted to core, color White - Red - Black (or to be agreed)	
Overall screen	Over the multipair will be shielded with aluminum/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminum/mylar tape and further mylar tape.	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armor :	SWA, Galvanized steel round wires Thickness : 0,9 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed) Thickness : 1,4 mm Overall diameter : 12,9 mm Total weight : 290 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 12,1 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 12 V. D. - Hydrocarbon and UV resistant	

Weight and diameter are theoretical + / - 10%