

**POWER CABLE**  
**Cu, PVC insulated, PVC outer sheath**  
**IEC60332.3, HT 105°C**

---

<b>Type</b>	<b>R-Cu/PVC/PVC 0,6/1Kv RR3OR 0,6/1Kv</b>	<b>3G 1,5sqmm</b>
<b>Conductor :</b>	Stranded plain copper conductor according to IEC60228 cl.2 size 1,5sqmm ( 7x0,53 ) Diam. 1,55 mm	
<b>Insulation :</b>	PVC extruded compound Thickness : 0,7 mm	- Temperature range -15 + 105°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to core, color Y/G - Blue - Brown	

<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound	
Color :	Black ( or to be agreed )	
Thickness :	1,8 mm	
Overall diameter :	9,4 mm	
Total weight :	130 Kg/Km	

**Marking :**

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

<b>Performance :</b>	- Conductor resistance	12,1 ohm/Km	( + 5% for multipair )
	- Test voltage core to core	3,5 Kv	
	- Flame retardant according to IEC60332-3-24, CEI20-22/3		
	- Low smoke and fume as per IEC60754-1, CEI20-37		
	- HCL emission $\leq$ 22%		
	- Minimum bending radius	12 V. D.	
	- Hydrocarbon resistant		
	- This cables are suitable for fixed installation in damp locations, in open spaces and for underground laying		

**Weight and diameter are theoretical +/- 10%**