

INSTRUMENTATION CABLE
Cu, XLPE insulated, individual and overall screen, LSZH outer sheath
IEC60332.3, EN50288-7

Type	R-Cu/XLPE/IS/OS/LSZH 300/500V RE4XHOHM1 300/500V	10X3X 0,75sqmm
Conductor :	Strandrd red copper conductor according to IEC60228 cl.2 size 0,75sqmm (7x0,37) Diam. 1,12 mm	
Insulation :	Cross-linked XLPE extruded compound Thickness : 0,55 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to triad, color White - Red - Black numbered (or to be agreed)	
Pair screen	Each pair will be shielded with aluminum/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminum/myler tape and further mylar tape.	
Overall screen	Over the multipair will be shielded with aluminum/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminum/myler tape and further mylar tape.	
Bedding :	Thickness : mm	
Armor :	Thickness : mm	
Outer sheath :	M1, Low Smoke Zero Halogen emission extruded compound Color : Black (or to be agreed) Thickness : 2,0 mm Overall diameter : 25 mm Total weight : 780 Kg/Km	
Marking :	On the outhter sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 24,5 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Low smoke density emission IEC61034-1/2 - Minimum bending radius 10 V. D. - Hydrocarbon resistant	

Weight and diameter are theoretical + / - 10%