

INSTRUMENTATION CABLE
Cu, XLPE insulated, individual and overall screen, PVC bedding, SWA, PVC outer sheath
IEC60332.3, EN50288-7

Type	R-Cu/XLPE/IS/OS/PVC/SWA/PVC 300/500V RE4XHOHRFR 300/500V	24X2X 0,5sqmm
Conductor :	Strandrd red copper conductor according to IEC60228 cl.2 size 0,5sqmm (7x0,30) Diam. 0,9 mm	
Insulation :	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to pairs, color White - Black numbered (or to be agreed)	
Pair screen	Each pair will be shielded with aluminum/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminum/myler tape and further mylar tape.	
Overall screen	Over the multipair will be shielded with aluminum/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminum/myler tape and further mylar tape.	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armor :	SWA, Galvanized steel round wires Thickness : 1,25 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed) Thickness : 2,0 mm Overall diameter : 34 mm Total weight : 1710 Kg/Km	
Marking :	On the outhter sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 36 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission </= 22% - Minimum bending radius 12 V. D. - Hydrocarbon resistant	

Weight and diameter are theoretical + / - 10%