

INSTRUMENTATION CABLE**Cu, XLPE insulated, individual and overall screen, PVC bedding, SWA, PVC outer sheath
IEC60332.1, IEC60332.3**

Type	R-Cu/XLPE/IS/OS/PVC/SWA/PVC 0,6/1Kv RE4XHOHRFR 0,6/1Kv	
Conductor :	Stranded red copper conductor according to IEC60228 cl.2 size 1,5sqmm (7x0,53) Diam. 1,55 mm	
Insulation :	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color White - Red - Black numbered (or to be agreed)	
Pair screen	Each pair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/mylar tape and further mylar tape.	
Overall screen	Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/mylar tape and further mylar tape.	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,2 mm	
Armor :	SWA, Galvanized steel round wires	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : dark Grey (or to be agreed)	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 12,1 ohm/Km (+ 5% for multipair) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Hydrocarbon and UV resistant	