

**INSTRUMENTATION CABLE
Cu, XLPE insulated, overall screen, LSZH outer sheath
IEC60332.3, IEC60754, IEC61034**

| | | |
|-----------------------|---|--|
| Type | R-Cu/XLPE/OS/LSZH 0,6/1Kv RE4OHM1 0,6/1Kv | 3X 1,5sqmm |
| Conductor : | Stranded plain copper conductor according to IEC60228 cl.2 size 1,5sqmm (7x0,53) Diam. 1,55 mm | |
| Insulation : | Cross-linked XLPE extruded compound Thickness : 0,7 mm | - Temperature range -20 + 90°C - Temperature laying -5 + 90°C |
| Laying up : | Twisted to core, color White - Red - Black (or to be agreed) | |
| Overall screen | Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm. | |
| Outer sheath : | M1, Low Smoke Zero Halogen emission extruded compound Color : Black (or to be agreed) Thickness : 1,8 mm Overall diameter : 9,6 mm Total weight : 130 Kg/Km | |
| Marking : | On the outer sheath " manufacturer's name year & description cable " with ink-jet printer. | |
| Performance : | - Conductor resistance 12,1 ohm/Km (+ 5% for multipair) - Test voltage core to core 3,5 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Low smoke density emission IEC61034-1/2 - Minimum bending radius 10 V. D. - Hydrocarbon and UV resistant - Inductance </= 0,90 mH/Km - Capacitance </= 0,250 microF/Km | |

Weight and diameter are theoretical + / - 10%