

**INSTRUMENTATION CABLE**  
**Cu, XLPE insulated, overall screen, LSZH bedding, SWA, LSZH outer sheath**  
**IEC60332.3, EN50288-7**

---

<b>Type</b>	<b>R-Cu/XLPE/OS/LSZH/SWA/LSZH 300/500V RE-2X(ST)H SWA H</b>	<b>5X 1,5sqmm</b>
<b>Conductor :</b>	Strandrd red copper conductor according to IEC60228 cl.2 size 1,5sqmm ( 7x0,53 ) Diam. 1,55 mm	
<b>Insulation :</b>	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, color Black numbered ( or to be agreed )	
<b>Overall screen</b>	Over the multipair will be shielded with aluminum/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminum/myler tape and further mylar tape.	
<b>Bedding :</b>	M1, Low Smoke Zero Halogen emission extruded compound Thickness : 1,0 mm	
<b>Armor :</b>	SWB, Galvanized steel braid wires Thickness : 0,9 mm	
<b>Outer sheath :</b>	M1, Low Smoke Zero Halogen emission extruded compound Color : Blue ( or to be agreed ) Thickness : 1,4 mm Overall diameter : 13,9 mm Total weight : 360 Kg/Km	
<b>Marking :</b>	On the outhter sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 12,1 ohm/Km (+ 5% for multipair ) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and halogen free as per IEC60754-2, CEI20-37/2 - Low smoke density emission IEC61034-1/2 - Minimum bending radius 12 V. D. - Hydrocarbon resistant	

**Weight and diameter are theoretical + / - 10%**