

**INSTRUMENTATION CABLE**  
**Cu, XLPE insulated, overall screen, PVC outer sheath**  
**IEC60332.3-24, EN50288-7**

---

<b>Type</b>	<b>R-Cu/XLPE/OS/PVC 300/500V</b> <b>RE-2X(st)Y-fl 300/500V</b>	<b>4X 1sqmm</b>
<b>Conductor :</b>	Stranded plain copper conductor according to IEC60228 cl.2 size 1sqmm ( 7x0,43 ) Diam. 1,3 mm	
<b>Insulation :</b>	Cross-linked XLPE extruded compound Thickness : 0,5 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, color Blue - Brown - Black - Grey ( or to be agreed )	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 50% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black ( or to be agreed ) Thickness : 1,8 mm Overall diameter : 8,8 mm Total weight : 130 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer. We confirm that the inkjet marking applied on our cables is durable for the period of the cable under normal conditions and practice, as per IEC international standards	
	<ul style="list-style-type: none"><li>- Conductor resistance 18,1 ohm/Km ( + 5% for multipair )</li><li>- Test voltage core to core 2 Kv</li><li>- Flame retardant according to IEC60332-3-24, CEI20-22/3</li><li>- Low smoke and fume as per IEC60754-1, CEI20-37</li><li>- HCL emission &lt;= 22%</li><li>- Minimum bending radius 8 V. D.</li><li>- Hydrocarbon UV resistant</li></ul>	

**Weight and diameter are theoretical +/- 10%**