

INSTRUMENTATION CABLE
Cu, XLPE insulated, overall screen, PVC bedding, SWB, PVC outer sheath
IEC60332.1, IEC60332.3, EN50288-7

Type	R-Cu/XLPE/OS/PVC/SWB/PVC 300/500V RE-2X(ST)Y SWB Y-fl	
Conductor :	Stranded red copper conductor according to IEC60228 cl.2 size 1,3sqmm (7x0,49) Diam. 1,3 mm	
Insulation :	Cross-linked XLPE extruded compound Thickness : 0,6 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to pair, color White - Black numbered (or to be agreed)	
Pair screen		
Overall screen	Over the multipair will be shielded with aluminium/mylar tape, with tinned copper drain wire 7x0,30 placed between the aluminium/mylar tape and further mylar tape.	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Armor :	SWB, Galvanized steel braid wires	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed)	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 14,8 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Hydrocarbon resistant	