

POWER CABLE
Cu, XLPE insulated, PVC bedding, SWA, PVC outer sheath
IEC60332.3

Type	F-Cu/XLPE/PVC/SWA/PVC 0,6/1Kv	2X 10sqmm
	FE4ORFR 0,6/1Kv	
Conductor :	Flexible plain copper conductor according to IEC60228 cl.5 size 10sqmm (77x0,40) Diam. 4,1 mm	
Insulation :	Cross-linked XLPE extruded compound	- Temperature range -20 + 90°C
	Thickness : 0,7 mm	- Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Blue - Brown (or to be agreed)	

Bedding : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Thickness : 1,0 mm

Armour : SWB, Galvanized steel braid wires
Thickness : 0,9 mm

Outer sheath : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Black (or to be agreed)
Thickness : 2,0 mm
Overall diameter : 22 mm
Total weight : 730 Kg/Km

Marking :

On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 1,91 ohm/Km (+ 5% for multipair)
- Test voltage core to core 4 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission \leq 22%
- Minimum bending radius 14 V. D.
- Hydrocarbon resistant

Weight and diameter are theoretical + / - 10%