

**INSTRUMENTATION CABLE
Cu, XLPE insulated, Cu overall screen, PVC outer sheath
IEC60332.3, IEC60502**

Type	R-Cu/XLPE/OS/PVC 0,6/1Kv RE4OH1R 0,6/1Kv	6X 2,5sqmm
Conductor :	Stranded plain copper conductor according to IEC60228 cl.2 size 2,5sqmm (7x0,67) Diam. 2 mm	
Insulation :	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color White numbered (or to be agreed)	
Overall screen	Applied over total assembly will be wrapped with polyester tape and shielded with Copper/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed) Thickness : 1,8 mm Overall diameter : 15 mm Total weight : 380 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 7,41 ohm/Km (+ 5% for multipair) - Test voltage core to core 3,5 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission \leq 22% - Minimum bending radius 10 V. D. - Hydrocarbon and UV resistant - Inductance \leq 0,90 mH/Km - Capacitance \leq 0,250 microF/Km	

Weight and diameter are theoretical + / - 10%