

**INSTRUMENTATION CABLE
Cu, XLPE insulated, Cu overall screen, PVC outer sheath
IEC60332.3, EN50288-7**

Type	R-Cu/XLPE/OS/PVC 300/500V RE4OH1R 300/500V	16X 1sqmm
Conductor :	Stranded plain copper conductor according to IEC60228 cl.2 size 1sqmm (7x0,43) Diam. 1,3 mm	
Insulation :	Cross-linked XLPE extruded compound Thickness : 0,5 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color White numbered (or to be agreed)	
Bedding :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
Screen :	PCT plain copper tape, 100% coverage 25% overlap Thickness : 0,1 mm	
Outer sheath :	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black (or to be agreed) Thickness : 1,8 mm Overall diameter : 18 mm Total weight : 610 Kg/Km	
Marking :	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
Performance :	- Conductor resistance 18,1 ohm/Km (+ 5% for multipair) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 10 V. D. - Hydrocarbon and UV resistant - Inductance <= 0,90 mH/Km - Capacitance <= 0,250 microF/Km	

Weight and diameter are theoretical + / - 10%