

POWER CABLE
Cu, XLPE insulated, PVC bedding, SWA, PVC outer sheath
IEC60332.3, IEC60502

Type	R-Cu/XLPE/PVC/SWA/PVC 0,6/1Kv	4G 4sqmm
	RE4ORFR 0,6/1Kv	
Conductor :	Stranded plain copper conductor according to IEC60228 cl.2 size 4sqmm (7x0,85)	
	Diam.	2,5 mm
Insulation :	Cross-linked XLPE extruded compound	- Temperature range -20 + 90°C
	Thickness :	0,7 mm - Temperature laying -5 + 90°C
Laying up :	Twisted to core, color Y/G - Brown - Black - Grey (or to be agreed)	

Bedding : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Thickness : 1,0 mm

Armour : SWA, Galvanized steel round wires
Thickness : 0,9 mm

Outer sheath : PVC, Polyvinylchloride Low Smoke and Fume extruded compound
Color : Black (or to be agreed)
Thickness : 1,8 mm
Overall diameter : 17 mm
Total weight : 530 Kg/Km

Marking :
On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.

Performance :

- Conductor resistance 4,61 ohm/Km (+ 5% for multipair)
- Test voltage core to core 3,5 Kv
- Flame retardant according to IEC60332-3-24, CEI20-22/3
- Low smoke and fume as per IEC60754-1, CEI20-37
- HCL emission \leq 22%
- Minimum bending radius 14 V. D.
- Hydrocarbon and UV resistant

- Inductance \leq 0,90 mH/Km
- Capacitance \leq 0,250 microF/Km

Weight and diameter are theoretical + / - 10%