

**POWER CABLE****Tinned Cu, PVC insulated, overall screen, PVC outer sheath  
IEC60332.3-24, EN50288-7**

---

<b>Type</b>	<b>R(t)-Cu/PVC/OS/PVC 300/500V RR2XOHR 300/500V</b>	<b>2X 1,5sqmm</b>
<b>Conductor :</b>	Stranded tinned copper conductor acc. to IEC60228 cl.2 size Diam. 1,55 mm	1,5sqmm ( 7x0,53 )
<b>Insulation :</b>	PVC extruded compound Thickness : 0,5 mm	- Temperature range -15 + 70°C - Temperature laying -5 + 70°C
<b>Laying up :</b>	Twisted to pair, color Blue - Black ( or to be agreed )	
<b>Overall screen</b>	Applied over total assembly will be wrapped with polyester tape and shielded with Aluminum/Mylar tape 100% coverage and 25% overlap with metal side in contact with a tinned copper drain wire 7x0,30 size 0,5sqmm.	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black ( or to be agreed ) Thickness : 1,2 mm Overall diameter : 8,5 mm Total weight : 120 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 13,7 ohm/Km (+ 5% for multipair ) - Test voltage core to core 2 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 8 V. D. - Hydrocarbon UV resistant  - Inductance <= 0,90 mH/Km - Capacitance <= 0,250 microF/Km	

**Weight and diameter are theoretical + / - 10%**