

**INSTRUMENTATION CABLE  
Cu, XLPE insulated, PVC bedding, SWA, PVC outer sheath  
IEC60332.3, IEC60502**

---

<b>Type</b>	<b>F-Cu/XLPE/PVC/SWA/PVC 0,6/1Kv FE4ORFR 0,6/1Kv</b>	<b>4X 16sqmm</b>
<b>Conductor :</b>	Flexible tinned copper conductor acc. to IEC60228 cl.5 Diam. 5,2 mm	size 16sqmm (7X18X0,40)
<b>Insulation :</b>	Cross-linked XLPE extruded compound Thickness : 0,7 mm	- Temperature range -20 + 90°C - Temperature laying -5 + 90°C
<b>Laying up :</b>	Twisted to core, color Y/G - Brown - Black - Grey ( or to be agreed )	
<b>Overall screen</b>		
<b>Bedding :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Thickness : 1,0 mm	
<b>Armor :</b>	SWA, Galvanized steel round wires Thickness : 1,25 mm	
<b>Outer sheath :</b>	PVC, Polyvinylchloride Low Smoke and Fume extruded compound Color : Black ( or to be agreed ) Thickness : 2,0 mm Overall diameter : 28 mm Total weight : 1550 Kg/Km	
<b>Marking :</b>	On the outer sheath " manufacturer's name year & description cable " with ink-jet printer.	
<b>Performance :</b>	- Conductor resistance 1,21 ohm/Km (+ 5% for multipair ) - Test voltage core to core 4 Kv - Flame retardant according to IEC60332-3-24, CEI20-22/3 - Low smoke and fume as per IEC60754-1, CEI20-37 - HCL emission <= 22% - Minimum bending radius 12 V. D. - Hydrocarbon resistant	

**Weight and diameter are theoretical + / - 10%**